

Plastique Royal 2809 Rue Etienne Lenoir Laval; H7R 6J4 QC

PRODUCT: DS503 BUTYL TAPE 5/16

Section 01: Chemical product and company identification

Product name..... DS503 BUTYL TAPE 5/16 Plastique Royal Inc., Manufactured for..... 2809 Rue Etienne-Lenoir

Laval, QC H7R 6J4

In Canada call Canutec (613) 996-6666 - In the United States call Chemtrec (800) 24 hour emergency number:.....

424-9300.

Material use..... Automotive. Chemical family..... Article.

Preparation date..... February 11, 2014.

Hazard rate

NFPA rating..... Health: 0 Fire: 0 Reactivity: 0.

HMIS..... H:0 F:0 R:0.

Section 02: Hazards identification

Signal Word..... Not classified. Hazard Classification..... Not classified. Hazard Description..... Not classified.

Precautionary Statements..... P202 Do not handle this product until all safety instructions have been read and

understood.

Note This product does not meet the OSHA Hazard Communication, Globally Harmonized

System or Workplace Hazardous Materials Information System criteria as a controlled or

classified product.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients CAS# Wt. %

PRODUCT IS AN ARTICLE AND NOT A Not applicable

CHEMICAL

CARBON BLACK 1333-86-4 100

10-30

Section 04: First aid measures

Flush for 15 minutes using plenty of water. If irritation persists seek medical attention. Eye contact.....

Skin contact..... Wash skin with soap and water. If irritation persists, seek medical attention.

Inhalation..... No specific treatment is necessary since this material is not likely to be hazardous by

Ingestion is unlikely. Contact a physician if unusual reaction is noted. In the event of an incident involving this product ensure that medical authorities are Ingestion..... Additional information.....

provided a copy of this safety data sheet.

Section 05: Fire fighting measures

Carbon dioxide, dry chemical, foam. Treat as a petroleum fire. Oxides of carbon (CO,CO2). Hydrocarbons. Extinguishing media.....

Hazardous combustion products.....

Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective

clothing to protect against potentially toxic and irritating fumes.

Section 06: Accidental release measures

Pick up solids and put in a dust bin. Keep in a suitable, closed container for disposal.

Section 07: Handling and storage

Handle in accordance with good industrial hygiene and safety practices. Employees should Handling procedures..... wash hands and face before eating or drinking. Keep away from heat, sparks, and open

Store in a cool and well ventilated area. Protect containers from physical damage. Do not Storage needs.....

store above 49C.

PRODUCT: DS503 BUTYL TAPE 5/16

Section 08: Exposure controls / personal protection

Protective equipment Where contact with this material is possible, eye protection is recommended. May cause Eye/type..... eye irritation after repeated or prolonged contact. Not applicable. Respiratory/type.....

Gloves/ type.....

Use of proper hygiene practices in the workplace is recommended. May cause skin

irritation after repeated or prolonged contact.

Clothing/type..... Wear long sleeves and trousers to prevent dermal exposure. May cause skin irritation after

repeated or prolonged contact. Safety boots per local regulations.

Footwear/type..... Educate and train employees on the safe use and handling of the product. Other/type..... Ventilation requirements...... Good general ventilation should be sufficient to control airborne levels.

Exposure limits

CARBON BLACK

OSHA PEL ACGIH TLV NIOSH Ingredients TWA STEL **PEL** STEL **REL** PRODUCT IS AN Not applicable Not applicable Not applicable Not applicable Not applicable ARTICLE AND NOT A CHEMICAL

3.5 mg/m3

No data

Not applicable

3.5 mg/m3

Section 09: Physical and chemical properties

No data

Physical state..... Black mastic, soft solid.

Colour..... Black.

Faint. Characteristic odour. Odour.....

Not applicable. Odour threshold (ppm)..... Vapour pressure (mm Hg)..... Not applicable. Vapour density (air=1)..... Not applicable. Not applicable. pH.....

3.5 mg/m3

Specific gravity.....

Freezing point (deg C)..... Not applicable. Not applicable. Solubility..... Boiling point (deg C)..... Not applicable. Not applicable. > 232 COC. Not applicable. Not applicable. Not applicable. Coefficient of water\oil distribution.....

Not applicable. 0.0 g/L - 0.0 lb/USG. VOC..... Not applicable. Viscosity.....

Section 10: Stability and reactivity

Stable at normal temperatures and pressures.

Reactivity conditions..... Avoid heat, sparks and flames.

Incompatibility......Hazardous products of decomposition....... Keep away from heat. Incompatible with strong solvents.

Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.

Hazardous polymerization..... Will not occur.

Section 11: Toxicological information

Route of entry Not expected to pose any hazards.

Effects of acute exposure..... May cause slight eye and slight skin irritation.

Effects of chronic exposure..... Prolonged or repeated contact may cause eye and skin irritation.

Carcinogenicity of material..... Not applicable.

Toxicological Data

CHEMICAL

LC50-inh, rat LD50-Oral,rat Ingredients

PRODUCT IS AN ARTICLE AND NOT A Not applicable

CARBON BLACK

No data >8,000 mg/kg oral (rat)

Section 12: Ecological information

Biodegradability...... No data.

PRODUCT: DS503 BUTYL TAPE 5/16

Section 13: Disposal considerations

Section 14: Transport information

Section 15: Regulatory information

EPA hazardous air pollutants (HAPS) None. 40CFR63

California Proposition 65.....

This product contains Carbon Black known to the State of California to cause cancer.

relate to its use in combination with any other material or in any other process.

Section 16: Other information

Prepared by: Regulatory Affairs. Telephone number: (800) 387-7981.