

Safety Data Sheet (SDS)

VERA SHINE Silicone Free High Gloss Dressing & Protectant



1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : VERA SHINE
Product identifier : NA-VSE
Product Family : SOLVENT BLEND

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses : Automotive Detailing

1.3 Details of the supplier of the safety data sheet

Company : NANOSKIN Car Care Products
Total Import Solutions, Inc.
14700 Radburn Ave.
Santa Fe Springs, CA 90670

Telephone : [562-691-6818](tel:562-691-6818)

Fax : [562-483-8333](tel:562-483-8333)

1.4 Emergency telephone number

Emergency phone # : PERS NORTH AMERICA 1-800-633-8253
INTERNATIONAL 1-801-629-0667

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910(OSHA HCS)

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Modified 1/10/2016

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.2 GHS Label elements, including precautionary statements

Pictogram



3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS number	Warnings	Concentration
Propylene glycol	7732-18-2		
STODDARD SOLVENT	64742-47-8	Flam. Liq. 4; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H227, H304, H315, H336, H411	>70%

4. FIRST AID MEASURES

First aid procedures

After inhalation:

Get victim to fresh air. Give artificial respiration or oxygen if breathing has stopped. Get prompt medical attention. Do not give fluids if victim is unconscious. If victim is conscious, rinse mouth with water and contact emergency number listed in section 1.4.

After contact with skin:

Immediately wash skin with soap and water. May cause irritation. Seek medical attention if irritation or allergic reaction is present.

After contact with eyes:

Immediately flush eyes with running water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek prompt medical attention if redness or irritation occurs. Avoid agitation. Remove contact lenses if able.

After ingestion:

Rinse mouth with water, contact poison control center or emergency number listed in section 1.4. Never give anything by mouth to an unconscious person.

Advice to doctor / Treatment:

None known.

5. FIRE FIGHTING MEASURES

FIRE HAZARD

Fire hazard : DIRECT FIRE HAZARD. Highly flammable. Gas/vapour flammable with air within explosion limits.

Modified 1/10/2016

INDIRECT FIRE HAZARD May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".

EXPLOSION HAZARD Gas/vapour explosive with air within explosion limits. **INDIRECT EXPLOSION** HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".

REACTIVITY Upon combustion: CO and CO₂ are formed. Violent to explosive reaction with many compounds. Prolonged storage: on exposure to light: release of harmful gases/vapours. Reacts violently with (strong) oxidizers: peroxidation resulting in increased fire or explosion risk.

FIREFIGHTING INSTRUCTIONS Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

PROTECTION DURING FIREFIGHTING Heat/fire exposure: compressed air/oxygen apparatus.

6. ACCIDENTAL RELEASE MEASURES

PROTECTIVE EQUIPMENT Gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus.

EMERGENCY PROCEDURES Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

FOR EMERGENCY RESPONDERS

PROTECTIVE EQUIPMENT Equip cleanup crew with proper protection.

EMERGENCY PROCEDURES Ventilate area.

SEE SECTION 8 FOR PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guideline Comments		Exposure Limits:		
COMPONENT	CAS NUMBER	VALUE	CONTROL PARAMETERS	BASIS
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm	2,000 mg/m ³
		OSHA Z-1 TWA	200 mg/m ³	(as total hydrocarbon vapor)
		ACGIH TWA	400 ppm	1,600 mg/m ³

ENGINEERING CONTROLS Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Materials for protective clothing : Use butyl rubber of at least .3mm thickness. Avoid nitrile and pvc protection.

Hand protection Please use gloves with the above materials recommendation.

Eye protection Protective goggles.

Modified 1/10/2016

Skin and body protection	Head/neck protection. Protective clothing.
Respiratory protection	Wear gas mask with filter type A if conc. in air > exposure limit.
Other information	Do not eat, drink or smoke during use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	liquid
Appearance	Green
Particle Size	Not applicable
Odor	bubblegum
Odor Threshold	No Available Data
Molecular Formula	Mixture
Molecular Weight	Mixture
Boiling Point	200 - 300 °C
Decomposition Temperature	No Available Data
Melting point	No Available Data
Freezing Point	No Available Data
Relative Density	~.825g/cm ³
Bulk Density	No Available Data
Solubility in Water	No Available Data
Solubility in other liquids	No Available Data
Flash point	80 - 96 °C

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Conditions to Avoid	Avoid extreme temperatures.
Hazardous Decomposition	
Products	Carbon Oxides.
Possibility of Hazardous Reactions	Do not bring into contact with oxidizers.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY****Solvent naphtha (petroleum), heavy aliph.**

64742-47-8: Acute oral toxicity : LD50 (rat, male and female): > 5,000 mg/kg
 Method: Fixed dose procedure GLP: yes Acute inhalation toxicity : Remarks:
 No data available Acute dermal toxicity : LD50 (rabbit, male and female): >
 2,000 mg/kg Method: Fixed dose procedure GLP: yes

12. ECOLOGICAL TOXICITY**TOXICITY****Solvent Naphtha (petroleum), heavy aliph.**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 25 mg/l Exposure time: 96 h
 Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes

13. DISPOSAL CONSIDERATIONS

Product Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed

Modified 1/10/2016

disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging Dispose of as unused product.

14. TRANSPORT INFORMATION

Shipping Information

DOT (US)

NA-Number: 1993 Class: NONE Packing group: III

Proper shipping name: Combustible liquid, n.o.s.

Reportable Quantity (RQ):

Poison Inhalation Hazard: No IMDG UN number: 1223 Class: 3 Packing group: III EMS-No: F-E, S-E

Proper shipping name: KEROSENE

Marine pollutant:yes IATA UN number: 1223 Class: 3 Packing group: III

Special Shipping Information

Not applicable.

HMIS

HEALTH **2**

FLAMMABILITY **2**

REACTIVITY **0**

15. REGULATORY INFORMATION

United States

SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313:

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Pennsylvania Right To Know Components

64742-47-8 Distillates (petroleum), hydrotreated light 0 - 100 %

64742-96-7 Solvent naphtha (petroleum), heavy aliph

New Jersey Right To Know Components

64742-47-8 Distillates (petroleum), hydrotreated light 0 - 100 %

64742-96-7 Solvent naphtha (petroleum), heavy aliph

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

SDS Prepared by

Total Import Solutions, Inc. dba NANOSKIN Car Care Products

Disclaimer

This health and safety information is correct to the best of our knowledge and belief at the date of its publication, but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, to maintain revised copies of this information to be requested. When applicable, revised copies shall be sent to customers whom

Modified 1/10/2016

have been directly supplied with this substance. It must be known that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the user. The information given in the Data Sheet is designed only as guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this sheet.