



TECHNICAL DATA SHEET

US

Distributed exclusively in North America by:

US Chemical & Plastics

A Division of Alco Industries Inc.

600 Nova Drive S.E., Massillon, Ohio 44646

330-830-6000

www.uschem.com

Gun Cleaner

Prod. No. 3 680 095

TECHNOLOGY

SprayMax®

- High productivity
- Easy application
- Constant atomization pressure during the total application process
- Finest aerosol dispersion

PRODUCT

Special cleaner for the aerosol supported cleaning of spray guns:

- All-purpose cleaner for many solvent based and waterborne paints including two-pack systems
- Excellent dissolving and cleaning properties

PROCESSING

Suitable for:

- 1K solvent based paints like basecoats for automotive refinish
- 1K waterborne paints like waterborne basecoats for automotive refinish.
- Two-pack systems like 2K PUR primer surfacers, fillers, topcoats or 2K epoxy systems.

Proceeding:

1. After you finished your paint job spray your spraying gun thoroughly empty
2. Remove the paint cup and nozzle head.
3. Not later than 2 h after you have finalized your paint work rinse the inner part of your spray gun as well as the nozzle head using the lancet on the spray head of the aerosol.
4. Drain the spray gun
5. Reassemble your spray gun and dry it with compressed air.



TECHNICAL DATA SHEET

Disposal: The emptied aerosols are suitable for household collection.

CHARACTERISTICS

Basis of raw material:	Special combination of solvents
Solid content:	n/a
VOC value:	6.5 lbs/Gal (750 g/l)
Shelf life:	60 months / 70 °F (20 °C)
Remarks:	For professional use only

SprayMax® is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.