

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Aerosol 2K DTM Fueller Hellgrau, Schwarz
- **Article number (product ID.):** REZ709
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture:**
painting
FOR PROFESSIONAL USE ONLY
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Tel.: +49 6269 95 20
- **national:**
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
- **K-Nr.** 0001

Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word *Danger*

· Hazard-determining components of labelling:

Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate)
acetoneEpoxy resin with an average molecular weight of $700 \leq 1200$

n-butyl acetate

Fettsäuren, Tallöl, Verbindungen mit Oleylamin

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

EUH204 Contains isocyanates. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8	Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119472128-37-xxxx		

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 2)

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17-xxxx	Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate) ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	2.5-<5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-xxxx	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<5%
CAS: 25068-38-6 NLP: 500-033-5	Epoxy resin with an average molecular weight of 700≤1200 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-<2.5%
CAS: 110-12-3 EINECS: 203-737-8 Reg.nr.: 01-2119472300-51-xxxx	5-methylhexan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1-<2.5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<2.5%
CAS: 85711-55-3 Reg.nr.: 01-2119974148-28-xxxx	Fettsäuren, Tallöl, Verbindungen mit Oleylamin ⚠ STOT RE 2, H373; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1A, H317	<0.1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media -**
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 4)

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm
Long-term value: 95 mg/m³, 20 ppm
Sk

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

· Ingredients with biological limit values:**1330-20-7 xylene, mixture of isomers**

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Nitrile rubber, NBR

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 5)

· **Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

· **Eye protection:**

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: -24.9 °C

· **Flash point:**

<0 °C

Without propellant gas.

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

235 °C

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not determined.

· **Explosion limits:**

Lower:

2.6 Vol %

Upper:

18.6 Vol %

· **Vapour pressure at 20 °C:**

3,400 hPa

· **Density:**

Not determined.

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 6)

- | | |
|---------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 66.5 % |
| VOC (EU) | With propellant gas. Content given by weight.
66.47 % |
| · Solids content: | |
| 9.2 Other information | 33.5 %
No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
- | | | |
|--|----------|-----------|
| · LD/LC50 values relevant for classification: | | |
| ATE (Acute Toxicity Estimates) | | |
| Inhalative | LC50/4 h | 35.2 mg/l |
- **Primary irritant effect:**
 - **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
 - **Serious eye damage/irritation**
Causes serious eye irritation.
 - **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
 - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure**
May cause drowsiness or dizziness.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
 - **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 7)

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|-------------------------------------|---|
| 14.1 UN-Number | UN1950 |
| ADR, IMDG, IATA | |
| 14.2 UN proper shipping name | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| ADR | AEROSOLS (trizinc bis(orthophosphate), zinc oxide), |
| IMDG | MARINE POLLUTANT |
| IATA | AEROSOLS, flammable |

14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1



- **Class**
- **Label**



- **Class**

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 8)

· **Label** 2.1· **IATA**· **Class** 2.1· **Label** 2.1· **14.4 Packing group**· **ADR, IMDG, IATA** Void
not classified· **14.5 Environmental hazards:**Product contains environmentally hazardous substances:
trizinc bis(orthophosphate)· **Marine pollutant:**Yes
Symbol (fish and tree)· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**-
not classified· **EMS Number:**

F-D,S-U

· **Stowage Code**SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear
of living quarters.· **Segregation Code**SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.· **14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
HAZARDOUS

GB

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 9)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
VOC: <840g/l

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	50-100

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol 2K DTM Fueller Hellgrau, Schwarz

(Contd. of page 10)

Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - dermal – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 . * **Data compared to the previous version altered.**

GB