



CCOAT
0518

COLOR COAT™



REFINISH INTERIORS



FORMULATED TO RESTORE OR CHANGE COLOR ON:

Flexible Plastic | Rigid Plastic | Vinyl | Carpet | Velour & More



MIXING SYSTEMS
THOUSANDS OF OEM MATCHED COLORS
AT SEMPRODUCTS.COM/EZMIX



50 POPULAR AEROSOL COLORS
& 3 CLEARS



CUSTOM FILL™ AEROSOL
BLANK (FILLON MACHINE)



UNIVERSAL COLOR COAT
BLANK (OMNI-FILL & OTHERS)





INSTRUCTIONS For full details, refer to the Technical Data Sheet.

STEP 1 PREP

VINYL & PLASTIC: Clean first with **SEM Soap** and a gray scuff pad. Rinse with water and allow to dry.

For vinyl, clean thoroughly with **Vinyl Prep** or **XXX Universal Surface Cleaner**. using a clean, damp, lint-free towel and wiping in one direction. For plastic, clean with **Plastic & Leather Prep** or **XXX Universal Surface Cleaner**.

CARPET & VELOUR: Shampoo first. Clean with **Plastic & Leather Prep**. Scrub lightly with a nylon bristle brush to separate the fibers and to remove oil, grease and contaminants. Allow to dry, then vacuum.

STEP 2 MIXING

DO NOT THIN. **Color Coat** is ready to spray.

Shake or stir well, per label instructions, to ensure color uniformity. For best results, use only when can temperature is approximately 70°F (21°C).

For additional versatility when matching low gloss OEM colors, **Color Coat Flattener** is available.



SEM Soap

A mild abrasive cleaner for flexible substrates.

Part	Size
39362	16 oz. Tube



Vinyl Prep

A strong solvent blend for refinishing vinyl.

Part	Size
38343	16 oz. Aerosol
38344	Quart



Plastic & Leather Prep

A mild solvent blend to clean plastic and leather.

Part	Size
38351	Square Gallon
38353	16 oz. Aerosol
38354	Cone Top Quart



Color Coat Flattener

An additive that lowers gloss and adds versatility.

Part	Size
13038	Pint



Custom Fill+™ High Build Aerosol Blank

A blank aerosol for filling custom Color Coat colors.

Part	Size
62013	16 oz. Aerosol



Universal Color Coat Blank

A blank aerosol for filling custom Color Coat colors.

Part	Size
15993	16 oz. Aerosol

STEP 3 APPLY

AEROSOL: Hold can approximately 6 – 8" from the surface. Apply light coats allowing 5 – 10 minutes between coats.

SPRAY GUN: Using fluid tip size 1.0 – 1.3 at 20 – 25 psi with non-HVLP or 8 – 10 psi at the cap with HVLP, apply 2 – 3 light coats or until hiding, allowing 5 – 10 minutes flash time between coats. Some colors will require more coats to cover.

CARPET & VELOUR: Spray one light coat and immediately brush in all directions using a nylon bristle brush. Apply a second light coat and brush again. After surface has completely dried, brush again to loosen fibers.



Mixing System Cone Top

For the jobber, shop or mobile technician: 9 toners and 3 clears.

Part	Size
27979	Cone Top Quart



Mixing System Quart

For the jobber or shop to start mixing Color Coat.

Part	Size
27989	Quart



Mixing System Gallon

For the jobber or shop that mixes Color Coat regularly.

Part	Size
27969	Gallon



SEM Products, Inc.
Rock Hill, SC 29730
1-800-831-1122
semproducts.com



Learn about Color Coat
semproducts.com/color-coat